



2022 AFRICA TWIN DCT SPECIFICATIONS*

ENGINE

Engine Type	1084cc liquid-cooled Unicam® four-stroke 22.5° parallel-twin
Bore And Stroke	92mm x 81.5mm
Compression Ratio	10.1:1
Induction	PGM-FI electronic fuel injection (Throttle By Wire)
Ignition	Full transistorized ignition
Starter	Electric

DRIVE TRAIN

Transmission	6-speed Automatic DCT
Final Drive	#525 Chain; 16T/42T

CHASSIS SUSPENSION BRAKES

Front Suspension	45mm inverted telescopic fork; 9.1 inches of travel
Rear Suspension	Pro-Link® system w/ single shock; 8.7 inches of travel
Front Brakes	Two four-piston hydraulic calipers w/ 310mm disks; ABS
Rear Brake	Single one-piston hydraulic caliper w/ 256mm disk; ABS
Front Tire	90/90-21
Rear Tire	150/70R-18

DIMENSIONS

Wheelbase	62 inches
Seat Height	Standard position 34.3 inches/Low position 33.5 inches
Curb Weight	529 lbs—Includes all standard equipment, required fluids and full tank of fuel—ready to ride
Fuel Capacity	5 gallons including 1.0-gallon reserve

OTHER

Model ID	CRF1100L
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Grand Prix Red

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.