



2024 AFRICA TWIN ADVENTURE SPORTS ES DCT SPECIFICATIONS*

ENGINE

Engine Type	1083cc liquid-cooled Unicam® four-stroke 22.5° parallel-twin
Bore And Stroke	92.0mm x 81.5mm
Compression Ratio	10.5:1
Valve Train	Unicam SOHC; four valves per cylinder
Induction	PGM-FI electronic fuel injection (Throttle By Wire)

DRIVE TRAIN

Transmission	6-speed Automatic DCT
Final Drive	#525 Chain; 16T/42T

CHASSIS SUSPENSION BRAKES

Front Suspension	45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel
Rear Suspension	Pro-Link® single shock with fork with electronic adjustment ; 7.9 inches of travel
Front Brakes	Dual 310mm discs with four-piston calipers; ABS
Rear Brake	Single 256mm disc with single-piston caliper; ABS
Front Tire	110/80-19
Rear Tire	150/70R-18

DIMENSIONS

Rake	27°
Trail	4.2 inches
Wheelbase	61.8 inches
Seat Height	Standard position 33.7 inches/Low position 32.9 inches
Curb Weight	559 lbs—Includes all standard equipment, required fluids and full tank of fuel—ready to ride
Fuel Capacity	6.6 gallons including 1.0-gallon reserve

OTHER

Model ID	CRF1100L4D
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	White

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.