



2024 NC750X DCT SPECIFICATIONS*

ENGINE

Engine Type	745cc liquid-cooled four-stroke 55° parallel-twin
Bore And Stroke	77.0mm x 80.0mm
Induction	PGM-FI; 36mm throttle body
Valve Train	SOHC; four valves per cylinder
Compression Ratio	10.7:1

DRIVE TRAIN

Transmission	Six-speed Automatic Dual Clutch Transmission (DCT)
Final Drive	#520 Chain; 17T/41T

CHASSIS SUSPENSION BRAKES

Front Suspension	41mm Showa telescopic fork; 4.7-inch travel
Rear Suspension	Pro-Link® single shock; 4.2-inch travel
Front Brake	Single 320mm wave disc; 2-channel ABS
Rear Brake	Single 240mm wave disc; 2-channel ABS
Front Tire	120/70ZR-17 radial
Rear Tire	160/60ZR-17 radial

DIMENSIONS

Rake (Caster Angle)	27.0°
Trail	4.3 inches
Wheelbase	60.1 inches
Seat Height	31.6 inches
Curb Weight	493 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride)
Fuel Capacity	3.8 gallons

OTHER

Model ID	NC750XD
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Matte Nightshade Blue

FACTORY WARRANTY INFORMATION

One Year	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.