



2024 TRANSALP SPECIFICATIONS*

ENGINE

Engine Type	755cc liquid-cooled 24.5° parallel-twin four-stroke
Bore And Stroke	87.0mm x 63.5mm
Compression Ratio	11.0:1
Valve Train	Unicam SOHC; four valves per cylinder
Induction	Programmed Fuel injection (PGM-FI); 46mm throttle body

DRIVE TRAIN

Transmission	Six-speed manual
Final Drive	#520 Chain; 16T/45T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm Showa SFF-CA inverted telescopic fork; 7.9-inch travel
Rear Suspension	Pro-Link® single Showa shock; 7.5-inch travel
Front Brake	Dual 310mm discs; 2-channel ABS
Rear Brake	Single 256mm disc; 2-channel ABS
Front Tire	90/90-21
Rear Tire	150/70-18

DIMENSIONS

Rake	27.0°
Trail	4.4 inches
Wheelbase	61.5 inches
Seat Height	33.7 inches (optional 32.6-inch accessory seat available)
Fuel Capacity	4.5 gallons
Curb Weight	459 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride)

OTHER

Model ID	XL750
Emissions	Meets current EPA and California Air Resources Board (CARB) standards.
Available Colors	Matte Black Metallic

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.