2026 AFRICA TWIN ADVENTURE SPORTS ES DCT SPECIFICATIONS*

ENGINE	
Engine Type	1084cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	92.0mm x 81.5mm
Compression Ratio	10.5:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Programmed Fuel-Injection system (PGM-FI); 46mm throttle body

DRIVETRAIN	
Transmission	Six-speed automatic Dual-Clutch Transmission (DCT)
Final Drive	#525 Chain; 16T/42T

CHASSIS SUSPENSION BRAKES	
Front Suspension	45mm inverted Showa® EERA® fork with electronic adjustment; 8.3 inches of travel
Rear Suspension	Pro-Link® Showa® single shock with electronic adjustment; 7.9 inches of travel
Front Brakes	Dual 310mm discs with radial-mounted four-piston calipers; ABS
Rear Brake	Single 256mm disc with single-piston caliper; ABS
Front Tire	110/80-19
Rear Tire	150/70R-18

DIMENSIONS	
Rake	27.5º
Trail	4.2 inches
Wheelbase	61.8 inches
Seat Height	33.7 inches (standard position)/32.9 inches (low position)
Curb Weight	559 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	6.6 gallons

OTHER	
Model ID	CRF1100L4D
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Pearl White

FACTORY WARRANTY INFORMATION	
Duration	Transferable, one-year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2026 American Honda Motor Co., Inc. – Powersports Division