



Image not found.

2022 REBEL 1100 SPECIFICATIONS*

ENGINE	
Engine Type	1084cc liquid-cooled Unicam® four-stroke 22.5° parallel-twin
Bore And Stroke	92mm x 81.5mm
Induction	PGM-FI electronic fuel injection (Throttle By Wire)
Ignition	Full transistorized ignition
Compression Ratio	10.1:1
Valve Train	SOHC; 4 valves per cylinder
DRIVE TRAIN	
Transmission	Six-Speed Manual
Final Drive	#525 O-ring-sealed chain; 16T/42T
CHASSIS SUSPENSION BRAKES	
Front Suspension	43mm fork; 4.8 inches of travel
Rear Suspension	Dual Showa shocks with 12.5mm shafts, adjustable preload, and piggyback pressurized reservoirs; 3.7 inches of travel
Front Brake	Single radial-mounted four-piston caliper with full-floating 330mm disc; ABS
Rear Brake	Single-caliper 256mm disc; ABS
Front Tire	130/70-18
Rear Tire	180/65-16
DIMENSIONS	
Rake (Caster Angle)	28° 0'
Trail	4.3 inches
Wheelbase	59.8 inches
Seat Height	27.5 inches
Curb Weight	487 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.6 gallons including 1.1-gallon reserve
Miles Per Gallon	TBD MPG - Honda's fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.
OTHER	
Model ID	CMX1100A
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Metallic Black, Bordeaux Red Metallic, Pearl Stallion Brown
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division