



2022 REBEL 500 ABS SE SPECIFICATIONS*

ENGINE	
Engine Type	471cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	67mm x 66.8mm
Induction	PGM-FI
Ignition	Full transistorized ignition
Compression Ratio	10.7:1
Valve Train	DOHC; 4 valves per cylinder
DRIVE TRAIN	
Transmission	Six-Speed
Final Drive	O-ring-sealed chain
CHASSIS SUSPENSION BRAKES	
Front Suspension	41mm fork; 4.8 inches of travel
Rear Suspension	Dual shocks with 3.8 inches of travel
Front Brake	Hydraulic disc; ABS
Rear Brake	Hydraulic disc; ABS
Front Tire	130/90-16
Rear Tire	150/80-16
DIMENSIONS	
Rake (Caster Angle)	28° 0'
Trail	4.3 inches
Wheelbase	58.7 inches
Seat Height	27.2 inches
Curb Weight	414 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	2.9 gallons
Miles Per Gallon	67 MPG - Honda fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.
OTHER	
Model ID	CMX500A2
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Matte Silver
FACTORY WARRANTY INFORMATION	
One Year	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.

©2022 American Honda Motor Co., Inc. – Powersports Division