



## 2023 REBEL 300 ABS SPECIFICATIONS\*

ENGINE	
Engine Type	286cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	76.0mm x 63.0mm
Induction	Programmed Fuel Injection (PGM-FI); 38mm throttle body
Valve Train	DOHC; four valves per cylinder
Compression Ratio	10.7:1
DRIVE TRAIN	
Transmission	Six-Speed
Final Drive	O-ring-sealed chain; 14T/36T
CHASSIS SUSPENSION BRAKES	
Front Suspension	41mm fork; 4.8-inch travel
Rear Suspension	Dual shocks; 5.5-inch travel
Front Brake	Single 296mm disc; ABS
Rear Brake	Single 240mm disc; ABS
Front Tire	130/90-16
Rear Tire	150/80-16
DIMENSIONS	
Rake (Caster Angle)	28.0°
Trail	4.3 inches
Wheelbase	58.7 inches
Seat Height	27.2 inches
Curb Weight	370 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	3.0 gallons
Miles Per Gallon	TBD MPG - Honda fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.
OTHER	
Model ID	CMX300A
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Candy Diesel Red, Matte Black Metallic
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

\*All figures are preliminary and subject to change.

©2023 American Honda Motor Co., Inc. – Powersports Division