



2023 REBEL 500 ABS SE SPECIFICATIONS*

ENGINE

Engine Type	471cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	67.0mm x 66.8mm
Induction	Programmed Fuel Injection (PGM-FI); 34mm throttle body
Valve Train	DOHC; 4 valves per cylinder
Compression Ratio	10.7:1

DRIVE TRAIN

Transmission	Six-speed manual
Final Drive	O-ring-sealed chain; 15T/40T

CHASSIS SUSPENSION BRAKES

Front Suspension	41mm fork; 5.5-inch travel
Rear Suspension	Dual shocks, 3.7-inch travel
Front Brake	Single 296mm disc; ABS
Rear Brake	Single 240mm disc; ABS
Front Tire	130/90-16
Rear Tire	150/80-16

DIMENSIONS

Rake	28.0°
Trail	4.3 inches
Wheelbase	58.7 inches
Seat Height	27.2 inches
Curb Weight	416 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.0 gallons

Miles Per Gallon	TBD - Honda fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.
------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

OTHER

Model ID	CMX500A2
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Titanium Metallic

FACTORY WARRANTY INFORMATION

One Year	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.