



2023 FURY SPECIFICATIONS*

ENGINE

Engine Type	1312cc liquid-cooled 52-degree V-twin four-stroke
Bore And Stroke	89.5mm x 104.3mm
Compression Ratio	9.2:1
Valve Train	SOHC; three valves per cylinder
Induction	PGM-FI, 38mm throttle body

DRIVE TRAIN

Transmission	Five-speed manual
Final Drive	Shaft

CHASSIS SUSPENSION BRAKES

Front Suspension	45mm fork; 5.1-inch travel
Rear Suspension	Single shock; 3.5-inch travel
Front Brake	Single 336mm disc with twin-piston caliper; ABS
Rear Brake	Single 296mm disc with single-piston caliper; ABS
Front Tire	90/90-21
Rear Tire	200/50-18

DIMENSIONS

Rake	32.0°
Trail	92mm (3.6 inches)
Wheelbase	71.0 inches
Seat Height	26.9 inches
Curb Weight	681 pounds (Includes all standard equipment, required fluids and a full tank of fuel.)
Fuel Capacity	3.4 gallons

Miles Per Gallon	45 MPG - Miles per gallon values are calculated estimates of fuel consumed during laboratory exhaust emissions tests specified by the EPA, not during on road riding. Use for comparison purposes only. Your actual mileage will vary depending on how you ride and maintain your vehicle, weather, road conditions, tire pressure, cargo and accessories, rider and passenger weight, and other factors.
------------------	---

OTHER

Model ID	VT1300CX
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Pearl Yellow

FACTORY WARRANTY INFORMATION

One Year Included	Unlimited-mileage, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.