



2024 REBEL 1100T SPECIFICATIONS*

ENGINE

Engine Type	1083cc liquid-cooled 22.5° parallel-twin four-stroke
Bore And Stroke	92.0mm x 81.5mm
Induction	PGM-FI electronic fuel injection; 46mm throttle body; throttle by wire
Valve Train	Unicam SOHC; 4 valves per cylinder
Compression Ratio	10.1:1

DRIVE TRAIN

Transmission	Six-speed with slipper/assist clutch
Final Drive	#525 O-ring-sealed chain; 16T/42T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm fork; 4.8-inch travel
Rear Suspension	Dual Showa shocks with 12.5mm shafts, adjustable preload, and piggyback pressurized reservoirs; 3.7-inch travel
Front Brake	Single 330mm disc with radial-mount four-piston caliper; ABS
Rear Brake	Single 256mm disc; ABS
Front Tire	130/70-18
Rear Tire	180/65-16

DIMENSIONS

Rake	28°
Trail	4.3 inches
Wheelbase	59.8 inches
Seat Height	27.5 inches
Curb Weight	520 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.6 gallons including 1.1-gallon reserve

OTHER

Model ID	CMX1100T
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Metallic Black, Matte Armored Green Metallic

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.