



## 2024 REBEL 300 SPECIFICATIONS\*

### ENGINE

Engine Type	286cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	76.0mm x 63.0mm
Induction	Programmed Fuel Injection (PGM-FI); 38mm throttle body
Valve Train	DOHC; four valves per cylinder
Compression Ratio	10.7:1

### DRIVE TRAIN

Transmission	Six-speed manual
Final Drive	O-ring-sealed chain; 14T/36T

### CHASSIS SUSPENSION BRAKES

Front Suspension	41mm fork; 4.8-inch travel
Rear Suspension	Dual shocks, 5.5-inch travel
Front Brake	Single 296mm disc; ABS
Rear Brake	Single 240mm disc; ABS
Front Tire	130/90-16
Rear Tire	150/80-16

### DIMENSIONS

Rake	28.0°
Trail	4.3 inches
Wheelbase	58.7 inches
Seat Height	27.2 inches
Curb Weight	364 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	3.0 gallons

### OTHER

Model ID	CMX300
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Candy Diesel Red, Matte Black Metallic

### FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

\*All figures are preliminary and subject to change.