



## 2024 FURY SPECIFICATIONS\*

### ENGINE

Engine Type	1312cc liquid-cooled 52-degree V-twin four-stroke
Bore And Stroke	89.5mm x 104.3mm
Compression Ratio	9.2:1
Valve Train	SOHC; three valves per cylinder
Induction	PGM-FI, 38mm throttle body

### DRIVE TRAIN

Transmission	Five-speed
Final Drive	Shaft

### CHASSIS SUSPENSION BRAKES

Front Suspension	45mm telescopic fork; 5.1-inch travel
Rear Suspension	Single shock with adjustable rebound damping and five-position spring-preload adjustability; 3.5-inch travel
Front Brake	Single 336mm disc with twin-piston caliper; ABS
Rear Brake	Single 296mm disc with single-piston caliper; ABS
Front Tire	90/90-21
Rear Tire	200/50-18

### DIMENSIONS

Rake (Caster Angle)	32.0°
Trail	92mm (3.6 inches)
Wheelbase	71.0 inches
Seat Height	26.9 inches
Curb Weight	675 pounds (Includes all standard equipment, required fluids and a full tank of fuel.)
Fuel Capacity	3.4 gallons

### OTHER

Model ID	VT1300CX
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Adventure Green

### FACTORY WARRANTY INFORMATION

One Year Included	Unlimited-mileage, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.