



2025 REBEL 1100T DCT SPECIFICATIONS*

ENGINE

Engine Type	1084cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	92.0mm x 81.5mm
Induction	Programmed Fuel Injection system (PGM-FI); 46mm throttle body
Valve Train	Unicam® SOHC; four valves per cylinder
Compression Ratio	10.1:1

DRIVETRAIN

Transmission	Six-speed automatic Dual-Clutch Transmission (DCT)
Final Drive	#525 O-ring-sealed chain; 16T/42T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm fork; 5.5-inch travel
Front Brake	Single 330mm disc with radial-mounted four-piston caliper; ABS
Rear Brake	Single 256mm disc; ABS
Front Tire	130/70-18
Rear Tire	180/65-16

DIMENSIONS

Rake	28.0°
Trail	4.3 inches
Wheelbase	59.8 inches
Seat Height	27.5 inches
Fuel Capacity	3.6 gallons
Curb Weight	542 pounds (includes all standard equipment, required fluids and a full tank of fuel)

OTHER

Model ID	CMX1100TD
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Gray Metallic

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.