2025 REBEL 500 SPECIFICATIONS*

ENGINE	
Engine Type	471cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	67.0mm x 66.8mm
Induction	Programmed Fuel Injection system (PGM-FI); 34mm throttle body
Valve Train	DOHC; four valves per cylinder
Compression Ratio	10.7:1

DRIVETRAIN	
Transmission	Six-speed manual
Final Drive	O-ring-sealed chain; 15T/40T

CHASSIS SUSPENSION BRAKES	
Front Suspension	41mm fork; 5.5-inch travel
Rear Suspension	Dual shocks; 3.7-inch travel
Front Brake	Single 296mm disc
Rear Brake	Single 240mm disc
Front Tire	130/90-16
Rear Tire	150/80-16

DIMENSIONS	
Rake	28.0°
Trail	4.3 inches
Wheelbase	58.6 inches
Seat Height	27.2 inches
Curb Weight	408 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.0 gallons

OTHER	
Model ID	CMX500
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Matte Black Metallic

FACTORY WARRANTY INFORMATION	
Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2026 American Honda Motor Co., Inc. – Powersports Division