



2025 FURY SPECIFICATIONS*

ENGINE

Engine Type	1312cc liquid-cooled V-twin four-stroke
Bore And Stroke	89.5mm x 104.3mm
Compression Ratio	9.2:1
Valve Train	SOHC; three valves per cylinder
Induction	Programmed Fuel-Injection system (PGM-FI); 38mm throttle body

DRIVETRAIN

Transmission	Five-speed manual
Final Drive	Shaft

CHASSIS SUSPENSION BRAKES

Front Suspension	45mm fork; 5.1-inch travel
Rear Suspension	Single shock; 3.7-inch travel
Front Brake	Single 336mm disc with twin-piston caliper; ABS
Rear Brake	Single 296mm disc; ABS
Front Tire	90/90-21
Rear Tire	200/50-18

DIMENSIONS

Rake	32.0°
Trail	3.6 inches
Wheelbase	71.0 inches
Seat Height	26.7 inches
Curb Weight	675 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.4 gallons

OTHER

Model ID	VT1300CX
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Adventure Green

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.