



## 2026 REBEL 1100 DCT SE SPECIFICATIONS\*

### ENGINE

Engine Type	1084cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	92.0mm x 81.5mm
Induction	PGM-FI electronic fuel injection; 46mm throttle body; throttle by wire
Valve Train	SOHC; four valves per cylinder
Compression Ratio	10.5:1

### DRIVETRAIN

Transmission	Six-speed automatic Dual-Clutch Transmission
Final Drive	#525 O-ring-sealed chain; 16T/42T

### CHASSIS SUSPENSION BRAKES

Front Suspension	43mm fork; 5.5-inch travel
Rear Suspension	Dual Showa® shocks, adjustable preload; 3.7-inch travel
Front Brake	Single 330mm disc with radial-mount four-piston caliper; ABS
Rear Brake	Single 256mm disc; ABS
Front Tire	130/70-18
Rear Tire	180/65-16

### DIMENSIONS

Rake	28.0°
Trail	4.3 inches
Wheelbase	59.8 inches
Seat Height	27.9 inches
Curb Weight	519 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.6 gallons

### OTHER

Model ID	CMX1100D3
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Deep Pearl Gray

### FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.