



2026 REBEL 1100 DCT SPECIFICATIONS*

ENGINE

Engine Type	1084cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	92.0mm x 81.5mm
Induction	PGM-FI electronic fuel injection; 46mm throttle body; throttle by wire
Valve Train	SOHC; four valves per cylinder
Compression Ratio	10.5:1

DRIVETRAIN

Transmission	Six-speed automatic Dual-Clutch Transmission
Final Drive	#525 O-ring-sealed chain; 16T/42T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm fork; 5.5-inch travel
Rear Suspension	Dual Showa® shocks, adjustable preload; 3.7-inch travel
Front Brake	Single 330mm disc with radial-mount four-piston caliper; ABS
Rear Brake	Single 256mm disc; ABS
Front Tire	130/70-18
Rear Tire	180/65-16

DIMENSIONS

Rake	28.0°
Trail	4.3 inches
Wheelbase	59.8 inches
Seat Height	27.9 inches
Curb Weight	518 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.6 gallons

OTHER

Model ID	CMX1100D
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Matte Black Metallic, Matte Silver Metallic

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.