



2026 REBEL 1100T SPECIFICATIONS*

ENGINE	
Engine Type	1084cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	92.0mm x 81.5mm
Induction	PGM-FI electronic fuel injection; 46mm throttle body; throttle by wire
Valve Train	Unicam® SOHC; four valves per cylinder
Compression Ratio	10.5:1
DRIVETRAIN	
Transmission	Six-speed manual
Final Drive	#525 O-ring-sealed chain; 16T/42T
CHASSIS SUSPENSION BRAKES	
Front Suspension	43mm fork; 5.5-inch travel; Dual Showa® shocks; 3.7-inch travel
Front Brake	Single 330mm disc with radial-mount four-piston caliper; ABS
Rear Brake	Single 256mm disc; ABS
Front Tire	130/70-18
Rear Tire	180/65-16
DIMENSIONS	
Rake	28.0°
Trail	4.3 inches
Wheelbase	59.8 inches
Seat Height	27.9 inches
Fuel Capacity	3.6 gallons
Curb Weight	528 pounds (includes all standard equipment, required fluids and a full tank of fuel)
OTHER	
Model ID	CMX1100T
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Gray Metallic
FACTORY WARRANTY INFORMATION	
Duration	Transferable, one year included, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.