



2026 REBEL 300 E-CLUTCH SPECIFICATIONS*

ENGINE

Engine Type	286cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	76.0mm x 63.0mm
Induction	Programmed Fuel Injection system (PGM-FI); 38mm throttle body
Valve Train	DOHC; four valves per cylinder
Compression Ratio	10.7:1

DRIVETRAIN

Transmission	Six-speed manual with Honda E-Clutch
Final Drive	#520 O-ring-sealed chain; 14T/36T

CHASSIS SUSPENSION BRAKES

Front Suspension	41mm fork; 5.5-inch travel
Rear Suspension	Dual shocks; 3.7-inch travel
Front Brake	Single 296mm disc
Rear Brake	Single 240mm disc
Front Tire	130/90-16
Rear Tire	150/80-16

DIMENSIONS

Rake	28.0°
Trail	4.3 inches
Wheelbase	58.7 inches
Seat Height	27.2 inches
Curb Weight	379 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.0 gallons

OTHER

Model ID	CMX300AC
Emissions	Meets current EPA and California Air Resources Board (CARB) standards
Available Colors	Matte Black Metallic; Pearl Smoky Gray

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.