



2026 REBEL 500 SPECIFICATIONS*

ENGINE

Engine Type	471cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	67.0mm x 66.8mm
Induction	Programmed Fuel Injection system (PGM-FI); 34mm throttle body
Valve Train	DOHC; four valves per cylinder
Compression Ratio	10.7:1

DRIVETRAIN

Transmission	Six-speed manual with slipper clutch
Final Drive	O-ring-sealed chain; 15T/40T

CHASSIS SUSPENSION BRAKES

Front Suspension	41mm fork; 5.5-inch travel
Rear Suspension	Dual shocks; 3.7-inch travel
Front Brake	Single 296mm disc; ABS
Rear Brake	Single 240mm disc; ABS
Front Tire	130/90-16
Rear Tire	150/80-16

DIMENSIONS

Rake	28.0°
Trail	4.3 inches
Wheelbase	58.7 inches
Seat Height	27.2 inches
Curb Weight	414 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.0 gallons

OTHER

Model ID	CMX500A
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Pearl Black, Pearl Smoky Gray

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.