



2022 CRF450RL SPECIFICATIONS*

ENGINE

Engine Type	449cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	96mm x 62.1mm
Compression Ratio	12.0:1
Valve Train	Unicam OHC, four-valve
Induction	Programmed Fuel Injection (PGM-FI), 46mm downdraft throttle body
Ignition	DC-CDI

DRIVE TRAIN

Transmission	Wide-ratio six-speed
Final Drive	#520 Chain; 13T/51T

CHASSIS SUSPENSION BRAKES

Front Suspension	49mm leading-axle inverted telescopic Showa coil-spring fork with rebound and compression damping adjustability; 12.0 inches of travel
Rear Suspension	Pro-Link Showa single shock with adjustable spring preload, rebound and compression damping adjustability; 11.8 inches of travel
Front Brake	Single 260mm disc with twin-piston caliper
Rear Brake	Single 240mm disc
Front Tire	IRC GP21 80/100-21
Rear Tire	IRC GP22 120/80-18

DIMENSIONS

Wheelbase	58.9 inches
Rake (Caster Angle)	28° 30'
Trail	4.8 inches
Seat Height	37.2 inches
Ground Clearance	12.6 inches
Fuel Capacity	2.0 gallons
Curb Weight	291 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride.)
Miles Per Gallon	TBD

OTHER

Available Colors	Red
Model ID	CRF450RL

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.