



## 2024 CRF300L ABS SPECIFICATIONS\*

### ENGINE

Engine Type	286cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	76mm x 63mm
Compression Ratio	10.7:1
Valve Train	DOHC; four-valve
Induction	PGM-FI, 38mm throttle body

### DRIVE TRAIN

Transmission	Six-speed manual
Final Drive	#520 chain; 14T/40T

### CHASSIS SUSPENSION BRAKES

Front Suspension	43mm inverted fork; 10.2-inch travel
Rear Suspension	Pro-Link® single shock; 10.2-inch travel
Front Brake	Single 256mm disc with twin-piston caliper; ABS
Rear Brake	Single 220mm disc; ABS
Front Tire	IRC GP21 80/100-21
Rear Tire	IRC GP22 120/80-18

### DIMENSIONS

Rake	27°30'
Trail	4.3 inches
Wheelbase	57.2 inches
Seat Height	34.7 inches
Ground Clearance	11.2 inches
Curb Weight	311 pounds
Fuel Capacity	2.1 gallons, including 0.5-gallon reserve

### OTHER

Available Colors	Red
Model ID	CRF300LA

### FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.