



2024 CRF300L RALLY SPECIFICATIONS*

ENGINE

Engine Type	286cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	76.0mm x 63.0mm
Compression Ratio	10.7:1
Valve Train	DOHC; four valves per cylinder
Induction	Programmed Fuel Injection (PGM-FI); 38mm throttle body

DRIVE TRAIN

Transmission	Six-speed
Final Drive	#520 chain; 14T/40T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm inverted fork; 10.2-inch travel
Rear Suspension	Pro-Link® single shock with adjustable spring preload; 10.2-inch travel
Front Brake	Single 296mm disc with twin-piston caliper
Rear Brake	Single 220mm disc
Front Tire	IRC GP21 80/100-21
Rear Tire	IRC GP 22 120/80-18

DIMENSIONS

Rake	27.5°
Trail	4.3 inches
Wheelbase	57.2 inches
Seat Height	35.2 inches
Ground Clearance	10.9 inches
Curb Weight	331 pounds
Fuel Capacity	3.4 gallons, including 0.6-gallon reserve

OTHER

Available Colors	Red
Model ID	CRF300LR

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.