



2024 XR650L SPECIFICATIONS*

ENGINE

Engine Type	644cc air-cooled dry-sump single-cylinder four-stroke
Bore And Stroke	100.0mm x 82.0mm
Compression Ratio	8.3:1
Valve Train	SOHC; four-valve RFVC™
Induction	42.5mm diaphragm-type CV carburetor

DRIVE TRAIN

Transmission	Five-speed manual
Final Drive	#520 O-ring-sealed chain; 15T/45T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm Showa® cartridge fork; 11.6-inch travel
Rear Suspension	Pro-Link® Showa® single-shock, 11.0-inch travel
Front Brake	Single 256mm disc with twin-piston caliper
Rear Brake	Single 220mm disc
Front Tire	3.00-21
Rear Tire	4.60-18

DIMENSIONS

Rake	27.0°
Trail	4.0 inches
Wheelbase	57.3 inches
Seat Height	37.0 inches
Curb Weight	346 pounds (Includes all standard equipment, required fluids and a full tank of fuel.)
Fuel Capacity	2.8 gallons, including 0.6-gallon reserve
Ground Clearance	13.0 inches

OTHER

Available Colors	White
Model ID	XR650L
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.