



2022 CRF250R SPECIFICATIONS*

ENGINE

Engine Type	249cc liquid-cooled single-cylinder four-stroke
Bore and Stroke	79.0mm x 50.9mm
Induction	Programmed Fuel-Injection system (PGM-FI); 44mm throttle bore
Ignition	DC-CDI
Compression Ratio	13.9:1
Starter	Electric with lithium-ion battery
Valve Train	DOHC, four valves per cylinder

DRIVETRAIN

Transmission	5-speed
Final Drive	#520 Chain; 13T/50T

CHASSIS SUSPENSION BRAKES

Front Suspension	49mm fully adjustable leading-axle inverted telescopic Showa® SPG coil-spring fork; 12.2 inches of travel
Rear Suspension	Pro-Link® system; fully adjustable Showa single shock; 12.3 inches of travel
Front Brake	Single 260mm hydraulic disc
Rear Brake	Single 240mm hydraulic disc
Front Tire	Pirelli Scorpion MX32 80/100-21 w/ tube
Rear Tire	Pirelli Scorpion MX32 100/90-19 w/ tube

DIMENSIONS

Rake (Caster Angle)	27° 19'
Trail	4.6 inches
Wheelbase	58.1 inches
Seat Height	37.8 inches
Curb Weight	229 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	1.7 gallons
Ground Clearance	13.1 inches
Length	85.7 inches
Width	32.6 inches
Height	49.8 inches

OTHER

Available Colors	Red
Model ID	CRF250R

*All figures are preliminary and subject to change.