



## 2024 CRF150R EXPERT SPECIFICATIONS\*

### ENGINE

|                   |   |
|-------------------|---|
| Engine Type       | 150cc liquid-cooled single cylinder                                   |
| Bore and Stroke   | 66mm x 43.8mm   |
| Compression Ratio | 11.7:1  |
| Valve Train       | Unicam SOHC; four valves per cylinder                                 |
| Induction         | 32mm Keihin flat-slide carburetor with Throttle Position Sensor (TPS) |

### DRIVE TRAIN

|              |                        |
|--------------|------------------------|
| Transmission | Close-ratio five-speed |
| Final Drive  | #420 chain; 15T/50T    |

### CHASSIS SUSPENSION BRAKES

|                  |   |
|------------------|---|
| Front Suspension | 37mm leading-axle inverted Showa cartridge fork with rebound- and compression-damping adjustability; 10.8-inch travel |
| Rear Suspension  | Pro-Link Showa single shock with spring-preload, rebound- and compression-damping adjustability; 10.7-inch travel     |
| Front Brake      | Single 220mm disc   |
| Rear Brake       | Single 190mm disc   |
| Front Tire       | Dunlop MX51; 70/100-19  |
| Rear Tire        | Dunlop MX51; 90/100-16  |

### DIMENSIONS

|                  |   |
|------------------|---|
| Rake             | 27.0°   |
| Trail            | 3.8 inches  |
| Wheelbase        | 50.6 inches   |
| Seat Height      | 34.1 inches   |
| Ground Clearance | 13.2 inches   |
| Curb Weight      | 187 pounds (Includes all standard equipment, required fluids and full tank of fuel) |
| Fuel Capacity    | 1.1 gallons   |

### OTHER

|                  |          |
|------------------|----------|
| Available Colors | Red      |
| Model ID         | CRF150RB |

\*All figures are preliminary and subject to change.