



2022 CBR300R ABS SPECIFICATIONS*

ENGINE

Engine Type	286cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	76mm x 63mm
Induction	PGM-FI, 38mm throttle body
Ignition	Computer-controlled digital transistorized with electronic advance
Compression Ratio	10.7:1
Valve Train	DOHC; four valves per cylinder

DRIVE TRAIN

Transmission	Six-speed
Final Drive	#520 Chain; 14T/36T

CHASSIS SUSPENSION BRAKES

Front Suspension	37mm telescopic fork; 4.65 inches of travel
Rear Suspension	Pro-Link® single shock with five positions of spring preload adjustability; 4.07 inches of travel
Front Brake	Single 296mm disc; ABS
Rear Brake	Single 220mm disc; ABS
Front Tire	110/70-17
Rear Tire	140/70-17

DIMENSIONS

Rake (Caster Angle)	25.3°
Trail	3.9 inches
Seat Height	30.7 inches
Fuel Capacity	3.4 gallons
Wheelbase	54.3 inches
Curb Weight	364 pounds - Includes all standard equipment, required fluids and full tank of fuel—ready to ride.

OTHER

Model ID	CBR300RA
Available Colors	Grand Prix Red, Matte Gray Metallic
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.