



2024 SCL500 SPECIFICATIONS*

ENGINE

Engine Type	471cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	67.0mm x 66.8mm
Compression Ratio	10.7:1
Valve Train	DOHC; four valves per cylinder
Induction	PGM-FI with 34mm throttle bodies

DRIVE TRAIN

Transmission	Six-speed
Final Drive	#520 O-ring-sealed chain; 15T/41T

CHASSIS SUSPENSION BRAKES

Front Suspension	41mm fork; 5.9-inch travel
Rear Suspension	Dual shocks with five-position spring-preload adjustability; 5.7-inch travel
Front Brake	Single 310mm disc with two-piston calipers; ABS
Rear Brake	Single 240mm disc, ABS
Front Tire	110/80-19
Rear Tire	150/70-17

DIMENSIONS

Rake	27.0°
Trail	4.3 inches
Wheelbase	58.4 inches
Seat Height	31.1 inches
Fuel Capacity	3.2 gallons
Curb Weight	423 pounds (Includes all standard equipment, required fluids and full tank of fuel)

OTHER

Model ID	SCL500A
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Candy Orange; Mat Laurel Green Metallic; Matte Black Metallic

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.