



2026 NT1100 DCT SPECIFICATIONS*

ENGINE

Engine Type	1084cc liquid-cooled parallel-twin four-stroke
Bore And Stroke	92.0mm x 81.5mm
Compression Ratio	10.5:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Programmed Fuel injection system (PGM-FI); 46mm throttle body

DRIVETRAIN

Transmission	Six-speed automatic Dual-Clutch Transmission (DCT)
Final Drive	#525 Chain; 16T/40T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm inverted Showa® SFF-BP fork; 5.9-inch travel
Rear Suspension	Pro-Link® Showa® single shock; 5.9-inch travel
Front Brake	Dual 310mm discs with radial-mounted four-piston calipers; ABS
Rear Brake	Single 256mm disc with single-piston caliper; ABS
Front Tire	120/70-17
Rear Tire	180/55-17

DIMENSIONS

Rake	26.5°
Trail	4.3 inches
Wheelbase	60.4 inches
Seat Height	32.3 inches (optional 32.6-inch accessory seat available)
Fuel Capacity	5.4 gallons
Curb Weight	547 pounds (includes all standard equipment, required fluids and a full tank of fuel)

OTHER

Model ID	NT1100D
Emissions	Meets current EPA and California Air Resources Board (CARB) standards.
Available Colors	Gray Metallic

FACTORY WARRANTY INFORMATION

Duration	Transferable, two-year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.