



2024 CRF250F SPECIFICATIONS*

ENGINE

Engine Type	250cc air-cooled single-cylinder four-stroke
Bore and Stroke	71.0mm x 63.0mm
Compression Ratio	9.6:1
Valve Train	SOHC; four-valves per cylinder
Induction	Fuel-injection, 34mm throttle bore

DRIVE TRAIN

Transmission	Five-speed
Final Drive	#520 O-ring-sealed chain; 13T/50T

CHASSIS SUSPENSION BRAKES

Front Suspension	41mm leading-axle Showa fork; 8.5-inch travel
Rear Suspension	Pro-Link® Showa single shock with spring-preload adjustability; 9.1-inch travel
Front Brake	Single 240mm disc
Rear Brake	Single 220mm disc
Front Tire	80/100-21
Rear Tire	100/100-18

DIMENSIONS

Rake (Caster Angle)	26.1°
Trail	4.0 inches
Wheelbase	55.9 inches
Seat Height	34.8 inches
Ground Clearance	11.3 inches
Curb Weight	265 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	1.6 gallons

OTHER

Model ID	CRF250F
Available Colors	Red
Emissions	Meets California Air Resources Board (CARB) and EPA off-road emissions standards.

FACTORY WARRANTY INFORMATION

Six Months Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.