



2024 CRF450X SPECIFICATIONS*

ENGINE

Engine Type	449cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	96.0mm x 62.1mm
Compression Ratio	12.0:1
Valve Train	Unicam® SOHC, four-valves per cylinder
Induction	Programmed Fuel Injection (PGM-FI), 46mm downdraft throttle body

DRIVE TRAIN

Transmission	Wide-ratio six-speed
Final Drive	#520 Chain; 13T/51T

CHASSIS SUSPENSION BRAKES

Front Suspension	49mm leading-axle inverted telescopic Showa coil-spring fork with rebound- and compression-damping adjustability; 12.0-inch travel
Rear Suspension	Pro-Link® Showa single shock with spring-preload, rebound- and compression-damping adjustability; 11.8-inch travel
Front Brake	Single 260mm disc with twin-piston caliper
Rear Brake	Single 240mm disc
Front Tire	Dunlop MX52 80/100-21
Rear Tire	Dunlop MX52 110/100-18

DIMENSIONS

Rake	27.6°
Trail	5.6 inches
Wheelbase	58.7 inches
Seat Height	37.9 inches
Ground Clearance	13.1 inches
Fuel Capacity	2.0 gallons
Curb Weight	275 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride)

OTHER

Available Colors	Red
Model ID	CRF450X

*All figures are preliminary and subject to change.