



2022 CRF250RX SPECIFICATIONS*

ENGINE	
Engine Type	249cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	79.0mm x 50.9mm
Induction	Programmed Fuel-Injection system (PGM-FI); 44mm throttle bore
Ignition	DC-CDI
Compression Ratio	13.9:1
Starter	Electric with lithium-ion battery
Valve Train	DOHC, four valves per cylinder
DRIVE TRAIN	
Transmission	5-speed
Final Drive	#520 Chain; 13T/50T
Clutch	Multiplate (5 springs)
CHASSIS SUSPENSION BRAKES	
Front Suspension	49mm fully adjustable leading-axle inverted telescopic Showa coil-spring fork; 12.2 inches of travel
Rear Suspension	Pro-Link® system; fully adjustable Showa single shock; 12.3 inches of travel
Front Brake	Single 260mm hydraulic disc
Rear Brake	Single 240mm hydraulic disc
Front Tire	Dunlop Geomax AT81 90/90-21
Rear Tire	Dunlop Geomax AT81 110/100-18
DIMENSIONS	
Rake (Caster Angle)	27° 9'
Trail	4.5 inches
Wheelbase	58.1 inches
Seat Height	38 inches
Curb Weight	238 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	2.21 gallons
Ground Clearance	13.2 inches
Length	85.7 inches
Width	33 inches
Height	50.4 inches
OTHER	
Available Colors	Red
Model ID	CRF250RX

*All figures are preliminary and subject to change.

©2021 American Honda Motor Co., Inc. – Powersports Division