



2022 CRF450RWE SPECIFICATIONS*

ENGINE	
Engine Type	449cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	96mm x 62.1mm
Compression Ratio	13.5:1
Valve Train	Unicam four-valve; 38mm intake, titanium; 31mm exhaust, Steel
Induction	Programmed Fuel Injection (PGM-FI), 46mm downdraft throttle body
Ignition	DC-CDI
DRIVE TRAIN	
Transmission	Close-ratio five-speed
Final Drive	#520 Chain; 13T/49T
CHASSIS SUSPENSION BRAKES	
Front Suspension	49mm inverted Showa fork with rebound and compression damping adjustability; 12.2 inches of travel (Titanium Nitride-coated lower fork legs)
Rear Suspension	Pro-Link Showa single shock with adjustable spring preload, rebound and compression damping adjustability; 12.4 inches of travel
Front Brake	Single 260mm disc with twin-piston caliper
Rear Brake	Single 240mm disc
Front Tire	Dunlop MX33 80/100-21
Rear Tire	Dunlop MX33 120/80-19
DIMENSIONS	
Wheelbase	58.3 inches
Rake (Caster Angle)	27° 7'
Trail	4.5 inches
Seat Height	38 inches
Ground Clearance	13.2 inches
Fuel Capacity	1.7 gallons
Curb Weight	244 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride.)
OTHER	
Available Colors	Red
Model ID	CRF450RWE

*All figures are preliminary and subject to change.

©2022 American Honda Motor Co., Inc. – Powersports Division