



## 2023 CRF450R SPECIFICATIONS\*

ENGINE	
Engine Type	450cc liquid-cooled single-cylinder
Bore And Stroke	96mm x 62.1mm
Compression Ratio	13.5:1
Valve Train	Unicam SOHC; four valves per cylinder
Induction	Programmed Fuel Injection (PGM-FI), 44mm downdraft throttle body
DRIVE TRAIN	
Transmission	Close-ratio five-speed
Final Drive	#520 Chain; 13T/49T
CHASSIS SUSPENSION BRAKES	
Front Suspension	49mm inverted Showa fork with 13-position rebound and 15-position compression-damping adjustability; 12.2-inch travel
Rear Suspension	Pro-Link Showa single shock with adjustable spring preload, 11-position rebound and six-position high- and low-speed compression-damping adjustability; 12.4-inch travel
Front Brake	Single 260mm disc with twin-piston caliper
Rear Brake	Single 240mm disc
Front Tire	Dunlop MX33 80/100-21
Rear Tire	Dunlop MX33 120/80-19
DIMENSIONS	
Wheelbase	58.3 inches
Rake (Caster Angle)	27.1°
Trail	4.5 inches
Seat Height	38 inches
Ground Clearance	13.2 inches
Fuel Capacity	1.7 gallons
Curb Weight	245 pounds (Includes all standard equipment, required fluids and full tank of fuel)
OTHER	
Available Colors	Red
Model ID	CRF450R

\*All figures are preliminary and subject to change.

©2022 American Honda Motor Co., Inc. – Powersports Division