



## 2019 CB500X ABS SPECIFICATIONS\*

### ENGINE

Engine Type	471cc liquid-cooled parallel-twin
Bore And Stroke	67mm x 66.8mm
Compression Ratio	10.7:1
Induction	PGM-FI with 34mm throttle bodies
Ignition	Computer-controlled digital transistorized with electronic advance
Valve Train	DOHC; four valves per cylinder

### DRIVE TRAIN

Transmission	Six-speed
Final Drive	O-ring-sealed chain

### CHASSIS SUSPENSION BRAKES

Front Suspension	41mm fork; 5.9 inches of travel
Rear Suspension	Pro-Link® single shock with nine-position spring preload adjustability; 5.9 inches of travel
Front Brake	320mm disc; ABS
Rear Brake	240mm disc; ABS
Front Tire	110/80-19
Rear Tire	160/60-17

### DIMENSIONS

Rake	27.5 degrees
Trail	108mm (4.3 inches)
Wheelbase	56.9 inches
Seat Height	32.7 inches
Fuel Capacity	4.6 gallons
Curb Weight	434 pounds

### OTHER

Model ID	CB500XA
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Grand Prix Red

### FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

\*All figures are preliminary and subject to change.