



## 2020 CB500X ABS SPECIFICATIONS\*

### ENGINE

Engine Type	471cc liquid-cooled parallel-twin
Bore And Stroke	67mm x 66.8mm
Compression Ratio	10.7:1
Induction	PGM-FI with 34mm throttle bodies
Ignition	Computer-controlled digital transistorized with electronic advance
Valve Train	DOHC; four valves per cylinder

### DRIVE TRAIN

Transmission	Six-speed
Final Drive	#520 O-ring-sealed chain; 15T/41T

### CHASSIS SUSPENSION BRAKES

Front Suspension	41mm fork; 5.9 inches of travel
Rear Suspension	Pro-Link® single shock with nine-position spring preload adjustability; 5.3 inches of travel
Front Brake	310mm disc; ABS
Rear Brake	240mm disc; ABS
Front Tire	110/80-19
Rear Tire	160/60-17

### DIMENSIONS

Rake	27.5 degrees
Trail	108mm (4.3 inches)
Wheelbase	56.8 inches
Seat Height	32.7 inches
Fuel Capacity	4.7 gallons
Curb Weight	434 pounds (Includes all standard equipment, required fluids and full tank of fuel-ready to ride)

### OTHER

Model ID	CB500XA
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Grand Prix Red

### FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

\*All figures are preliminary and subject to change.