



2021 CB500X ABS SPECIFICATIONS*

ENGINE	
Engine Type	471cc liquid-cooled parallel-twin
Bore And Stroke	67mm x 66.8mm
Compression Ratio	10.7:1
Induction	PGM-FI with 34mm throttle bodies
Ignition	Computer-controlled digital transistorized with electronic advance
Valve Train	DOHC; four valves per cylinder
DRIVE TRAIN	
Transmission	Six-speed
Final Drive	#520 O-ring-sealed chain; 15T/41T
CHASSIS SUSPENSION BRAKES	
Front Suspension	41mm fork; 5.9 inches of travel
Rear Suspension	Pro-Link® single shock with nine-position spring preload adjustability; 5.3 inches of travel
Front Brake	310mm disc; ABS
Rear Brake	240mm disc; ABS
Front Tire	110/80-19
Rear Tire	160/60-17
DIMENSIONS	
Rake	27.5 degrees
Trail	108mm (4.3 inches)
Wheelbase	56.8 inches
Seat Height	32.8 inches
Fuel Capacity	4.7 gallons
Curb Weight	434 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride.)
OTHER	
Model ID	CB500XA
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Matte Black Metallic
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.

©2020 American Honda Motor Co., Inc. – Powersports Division