



2022 AFRICA TWIN ADVENTURE SPORTS ES SPECIFICATIONS*

ENGINE	
Engine Type	1084cc liquid-cooled Unicam® four-stroke 22.5° parallel-twin
Bore And Stroke	92mm x 81.5mm
Valve Train	SOHC; four valves per cylinder
Compression Ratio	10.1:1
Induction	PGM-FI electronic fuel injection (Throttle By Wire)
Ignition	Full transistorized ignition
Starter	Electric
DRIVE TRAIN	
Transmission	6-speed Manual
Final Drive	#525 Chain; 16T/42T
CHASSIS SUSPENSION BRAKES	
Front Suspension	45mm inverted telescopic fork; 9.1 inches of travel
Rear Suspension	Pro-Link® system w/ single shock; 8.7 inches of travel
Front Brakes	Two four-piston hydraulic calipers w/ 310mm disks; ABS
Rear Brake	Single one-piston hydraulic caliper w/ 256mm disk; ABS
Front Tire	90/90-21
Rear Tire	150/70R-18
DIMENSIONS	
Wheelbase	62 inches
Seat Height	Standard position 34.3 inches/Low position 33.5 inches
Curb Weight	529 lbs—Includes all standard equipment, required fluids and full tank of fuel—ready to ride
Fuel Capacity	6.5 gallons including 1.0-gallon reserve
OTHER	
Model ID	CRF1100L4
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	White
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, unlimited-mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.

©2022 American Honda Motor Co., Inc. — Powersports Division