



## 2022 FURY ABS SPECIFICATIONS\*

ENGINE	
Engine Type	1312cc liquid-cooled 52 degrees V-twin
Bore And Stroke	89.5mm x 104.3mm
Induction	PGM-FI, 38mm throttle body
Ignition	Digital with three-dimensional mapping, two spark plugs per cylinder
Compression Ratio	9.2:1
Valve Train	SOHC; three valves per cylinder
DRIVE TRAIN	
Transmission	Five-speed
Final Drive	Shaft
CHASSIS SUSPENSION BRAKES	
Front Suspension	45mm fork; 4.0 inches travel
Rear Suspension	Single shock with adjustable rebound-damping and five-position spring-preload adjustability; 3.7 inches travel
Front Brake	Single 336 mm disc with twin-piston caliper
Rear Brake	Single 296 mm disc with single-piston caliper
Front Tire	90/90-21
Rear Tire	200/50-18
DIMENSIONS	
Rake (Caster Angle)	32°
Trail	92mm (3.6 inches)
Wheelbase	71 inches
Seat Height	26.9 inches
Curb Weight	663 pounds (Includes all standard equipment, required fluids and a full tank of fuel ready to ride)
Fuel Capacity	3.4 gallons
Miles Per Gallon	45 MPG - Miles per gallon values are calculated estimates of fuel consumed during laboratory exhaust emissions tests specified by the EPA, not during on road riding. Use for comparison purposes only. Your actual mileage will vary depending on how you ride and maintain your vehicle, weather, road conditions, tire pressure, cargo and accessories, rider and passenger weight, and other factors.
OTHER	
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Pearl Yellow
Model ID	VT13CX
FACTORY WARRANTY INFORMATION	
One Year Included	Unlimited-mileage, limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

\*All figures are preliminary and subject to change.

©2022 American Honda Motor Co., Inc. – Powersports Division