



2019 XR650L SPECIFICATIONS*

| ENGINE | |
|------------------------------|---|
| Engine Type | 644cc air-cooled dry-sump single-cylinder four-stroke |
| Bore And Stroke | 100mm x 82mm |
| Compression Ratio | 8.3:1 |
| Valve Train | SOHC; four-valve RFVC™ |
| Induction | 42.5mm diaphragm-type CV carburetor |
| Ignition | Solid-state CD with electronic advance |
| DRIVE TRAIN | |
| Transmission | Five-speed |
| Final Drive | #520 O-ring-sealed chain; 15T/45T |
| CHASSIS SUSPENSION BRAKES | |
| Front Suspension | 43mm air-adjustable axle Showa® cartridge fork with 16-position compression-damping adjustability; 11.6-inches of travel |
| Rear Suspension | Pro-Link® Showa single-shock with spring-preload, 20-position compression- and 20-position rebound-damping adjustability; 11.0-inches of travel |
| Front Brake | Single disc with twin-piston caliper |
| Rear Brake | Single disc |
| Front Tire | 3.00-21 |
| Rear Tire | 4.60-18 |
| DIMENSIONS | |
| Rake | 27.0 degrees |
| Trail | 102mm (4.0 inches) |
| Wheelbase | 57.3 inches |
| Seat Height | 37.0 inches |
| Curb Weight | 346 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride) |
| Fuel Capacity | 2.8 gallons, including 0.6-gallon reserve |
| Ground Clearance | 13.0 inches |
| Miles Per Gallon | 52 MPG - Miles per gallon values are calculated estimates of fuel consumed during laboratory exhaust emissions tests specified by the EPA, not during on road riding. Use for comparison purposes only. Your actual mileage will vary depending on how you ride and maintain your vehicle, weather, road conditions, tire pressure, cargo and accessories, rider and passenger weight, and other factors. |
| OTHER | |
| Available Colors | Red |
| Model ID | XR650L |
| Emissions | Meets current California Air Resource Board (CARB) and EPA off-road emissions standards. |
| FACTORY WARRANTY INFORMATION | |
| One Year | Transferable limited warranty; extended coverage available with a Honda Protection Plan |

*All figures are preliminary and subject to change.