



2022 CRF300L ABS SPECIFICATIONS*

ENGINE

Engine Type	286cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	76mm x 63mm
Induction	PGM-FI, 38mm throttle body
Ignition	Computer-controlled digital transistorized with electronic advance
Compression Ratio	10.7:1
Valve Train	DOHC; four-valve

DRIVE TRAIN

Transmission	Six-speed
Final Drive	#520 chain; 14T/40T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm telescopic inverted fork; 10.2 inches of travel
Rear Suspension	Pro-Link® single shock with spring; 10.2 inches of travel
Front Brake	Single 256mm disc with twin-piston caliper; ABS
Rear Brake	Single 220mm disc; ABS
Front Tire	80/100-21
Rear Tire	120/80-18

DIMENSIONS

Rake (Caster Angle)	27°30'
Trail	4.3 inches
Wheelbase	57.2 inches
Seat Height	34.7 inches
Ground Clearance	11.2 inches
Curb Weight	311 pounds
Fuel Capacity	2.1 gallons, including 0.5-gallon reserve

Miles Per Gallon	TBD MPG - Honda fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.
------------------	---

OTHER

Available Colors	Red
Model ID	CRF300LA

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, unlimited mileage limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.