



2022 XR650L SPECIFICATIONS*

ENGINE

Engine Type	644cc air-cooled dry-sump single-cylinder four-stroke
Bore And Stroke	100mm x 82mm
Compression Ratio	8.3:1
Valve Train	SOHC; four-valve RFVC™
Induction	42.5mm diaphragm-type CV carburetor
Ignition	Solid-state CD with electronic advance

DRIVE TRAIN

Transmission	Five-speed
Final Drive	#520 O-ring-sealed chain; 15T/45T

CHASSIS SUSPENSION BRAKES

Front Suspension	43mm air-adjustable axle Showa® cartridge fork with 16-position compression-damping adjustability; 11.6 inches of travel
Rear Suspension	Pro-Link® Showa single-shock with spring-preload, 20-position compression- and 20-position rebound-damping adjustability; 11.0 inches of travel
Front Brake	Single disc with twin-piston caliper
Rear Brake	Single disc
Front Tire	3.00-21
Rear Tire	4.60-18

DIMENSIONS

Rake (Caster Angle)	27.0°
Trail	4.0 inches
Wheelbase	57.3 inches
Seat Height	37.0 inches
Curb Weight	346 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	2.8 gallons, including 0.6-gallon reserve
Ground Clearance	13.0 inches

Miles Per Gallon	52 MPG - Miles per gallon values are calculated estimates of fuel consumed during laboratory exhaust emissions tests specified by the EPA, not during on road riding. Use for comparison purposes only. Your actual mileage will vary depending on how you ride and maintain your vehicle, weather, road conditions, tire pressure, cargo and accessories, rider and passenger weight, and other factors.
------------------	---

OTHER

Available Colors	White
Model ID	XR650L
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.

©2022 American Honda Motor Co., Inc. — Powersports Division