



2020 SUPER CUB C125 ABS SPECIFICATIONS*

ENGINE	
Engine Type	124.9cc air-cooled single-cylinder four-stroke
Bore And Stroke	52.4mm x 57.9mm
Compression Ratio	9.3:1
Induction	PGM-FI with automatic enrichment
Ignition	Fully transistorized
Valve Train	SOHC; two valves per cylinder
DRIVE TRAIN	
Transmission	Four-speed semi-automatic
Final Drive	#420 Chain; 14T/36T
Clutch	Automatic centrifugal
CHASSIS SUSPENSION BRAKES	
Front Suspension	26mm telescopic fork; 3.5 inches travel
Rear Suspension	Twin shock; 3.6 inches travel
Front Brake	Single 220mm hydraulic disc; ABS
Rear Brake	Mechanical drum
Front Tire	70/90-17
Rear Tire	80/90-17
DIMENSIONS	
Rake	26.5°
Trail	2.8 inches
Wheelbase	48.9 inches
Seat Height	30.7 inches
Fuel Capacity	1.0 gallon
Curb Weight	240 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride)
Miles Per Gallon	TBD MPG - Honda's fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider weight, and other factors.
OTHER	
Model ID	C125A
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Pearl Nebula Red
FACTORY WARRANTY INFORMATION	
One Year	Unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.

*All figures are preliminary and subject to change.

©2020 American Honda Motor Co., Inc. – Powersports Division