



2022 CB500F ABS SPECIFICATIONS*

ENGINE	
Engine Type	471cc Liquid-Cooled Parallel-Twin
Bore And Stroke	67.0mm x 66.8mm
Compression Ratio	10.7:1
Induction	PGM-FI with 34mm throttle bodies
Ignition	Computer-controlled digital transistorized with electronic advance
Valve Train	DOHC; four valves per cylinder
DRIVE TRAIN	
Transmission	Six-speed
Final Drive	O-ring-sealed chain
CHASSIS SUSPENSION BRAKES	
Front Suspension	41mm Showa SFF-BP fork; 4.3 inches of travel
Rear Suspension	Pro-Link® single shock with nine-position spring preload adjustability; 4.7 inches travel
Front Brake	Twin four-piston calipers with 296mm discs; ABS
Rear Brake	Single-caliper 240mm disc, ABS
Front Tire	120/70R-17 radial
Rear Tire	160/60-17 radial
DIMENSIONS	
Rake (Caster Angle)	25.5°
Trail	4.0 inches
Wheelbase	55.5 inches
Seat Height	31.1 inches
Fuel Capacity	4.5 gallons
Curb Weight	416 pounds (Includes all standard equipment, required fluids and full tank of fuel-ready to ride.)
OTHER	
Model ID	CB500FA
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Matte Gray Metallic
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, unlimited-mileage, limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.

©2022 American Honda Motor Co., Inc. – Powersports Division