



## 2018 CB500F SPECIFICATIONS\*

ENGINE	
Engine Type	471cc Liquid-Cooled Parallel-Twin
Bore And Stroke	67.0mm x 66.8mm
Compression Ratio	10.7:1
Induction	PGM-FI with 34mm throttle bodies
Ignition	Computer-controlled digital transistorized with electronic advance
Valve Train	DOHC; four valves per cylinder
DRIVE TRAIN	
Transmission	Six-speed
Final Drive	O-ring-sealed chain
CHASSIS SUSPENSION BRAKES	
Front Suspension	41mm fork; 4.3 inches travel
Rear Suspension	Pro-Link® single shock with nine-position spring preload adjustability; 4.7 inches travel
Front Brake	Twin-piston caliper with single 320mm disc
Rear Brake	Single-caliper 240mm disc
Front Tire	120/70-17
Rear Tire	160/60-17
DIMENSIONS	
Rake	25.5 degrees (caster angle)
Trail	102mm (4.01 inches)
Wheelbase	55.5 inches
Seat Height	30.7 inches
Fuel Capacity	4.4 gallons
Curb Weight	414.4 pounds (Includes all standard equipment, required fluids and full tank of fuel - ready to ride)
OTHER	
Model ID	CB500F
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Candy Blue/Matte Black

\*All figures are preliminary and subject to change.

©2019 American Honda Motor Co., Inc. – Powersports Division