



2022 PIONEER 1000 TRAIL SPECIFICATIONS*

ENGINE	
Engine Type	999cc liquid-cooled twin-cylinder Unicam® four-stroke
Bore And Stroke	92.0mm x 75.15mm
Compression Ratio	10:1
Induction	Fuel Injection (PGM-FI), 44mm throttle body
Ignition	Full-transistorized with electronic advance
DRIVE TRAIN	
Transmission	Fully Automatic Dual Clutch Transmission (DCT) with six forward gears and Reverse. Four drive modes include 2WD, 4WD, Turf and Differential lock. Paddle Shifters with three shift modes (standard, sport, and manual)
Driveline	Direct front and rear driveshafts
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 10.6 inches of travel
Rear Suspension	Independent double-wishbone; 10 inches of travel
Front Brake	Dual 210mm hydraulic discs
Rear Brake	Dual 210mm hydraulic discs
Front Tires	27 x 9-14
Rear Tires	27 x 11-14
DIMENSIONS	
Length	120.4 inches
Width	63.0 inches
Height	76.1 inches
Wheelbase	80.2 inches
Bed Capacity	1000 pounds for 49 states
Bed Capacity	600 pounds for CA model
Towing Capacity	2500 pounds
Ground Clearance	12.8 inches
Turning Radius	13.8 feet
Curb Weight	1654 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.9 gallons, including 1.7-gallon reserve
OTHER	
Safety	Recommended for drivers 16 years of age and older.
Available Colors	Matte Silver
Model ID	SXS10M3DT
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.