



## 2024 PIONEER 1000-5 TRAIL SPECIFICATIONS\*

### ENGINE

Engine Type	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
Bore And Stroke	92.0mm x 75.2mm
Compression Ratio	10:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Fuel Injection (PGM-FI), 44mm throttle body

### DRIVE TRAIN

Transmission	Six-speed automatic Dual-Clutch Transmission (DCT)
Driveline	Direct front and rear driveshafts

### CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 10.5-inch travel
Rear Suspension	Independent double-wishbone; 10.0-inch travel
Front Brakes	Dual 210mm hydraulic discs
Rear Brakes	Dual 210mm hydraulic discs
Front Tires	27 x 9-14
Rear Tires	27 x 11-14

### DIMENSIONS

Length	119.2 inches
Width	63.0 inches
Height	76.5 inches
Wheelbase	80.2 inches
Bed Capacity	1000 pounds for 49-state models; 600 pounds for CA model
Towing Capacity	2500 pounds
Seat Height	33.8 inches
Ground Clearance	12.3 inches
Turning Radius	13.8 feet
Curb Weight	1777 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.9 gallons, including 1.2-gallon reserve

### OTHER

Safety	Recommended for drivers 16 years of age and older.
Available Colors	Matte Forged Bronze Metallic, Matte Metallic Blue
Model ID	SXS10M5DT

### FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.