



## 2024 PIONEER 1000-6 DELUXE CREW SPECIFICATIONS\*

### ENGINE

Engine Type	999cc longitudinally mounted liquid-cooled twin-cylinder four-stroke
Bore And Stroke	92.0mm x 75.2mm
Valve Train	Unicam® SOHC; four valves per cylinder
Compression Ratio	10:1
Induction	Programmed Fuel Injection (PGM-FI); 44mm throttle body

### DRIVE TRAIN

Transmission	Fully automatic Dual Clutch Transmission (DCT) with six forward gears, reverse, high/low subtransmission and paddle shifters; four drive modes (2WD, 4WD, Turf and Differential Lock); three shift modes (Standard, Sport, and Manual)
Driveline	Direct front and rear driveshafts

### CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 10.5-inch travel
Rear Suspension	Independent double-wishbone; 10.0-inch travel
Front Brake	Dual 210mm discs
Rear Brake	Dual 210mm discs
Front Tires	27 x 9-14
Rear Tires	27 x 11-14

### DIMENSIONS

Length	152.2 inches
Width	63.0 inches
Height	76.1 inches
Wheelbase	115.2 inches
Bed Capacity	1000 pounds (49 states); 600 pounds (CA model)
Towing Capacity	2500 pounds
Ground Clearance	12.6 inches
Turning Radius	18.7 feet
Curb Weight	1936 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.9 gallons, including 1.7-gallon reserve

### OTHER

Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Avenger Red, Black Forest Green, TrueTimber® Atera Camo
Model ID	SXS10M6D

### FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

\*All figures are preliminary and subject to change.