2025 PIONEER 1000 TRAIL SPECIFICATIONS*

ENGINE	
Engine Type	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
Bore And Stroke	92.0mm x 75.1mm
Compression Ratio	10.0:1
Valve Train	Unicam® SOHC; four valves per cylinder
Induction	Programmed Fuel injection system (PGM-FI); 44mm throttle body

DRIVETRAIN	
Transmission	Six-speed automatic Dual-Clutch Transmission (DCT)
Driveline	Direct front and rear driveshafts

CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 10.6-inch travel
Rear Suspension	Independent double-wishbone; 10.0-inch travel
Steering	Electric Power Steering (EPS)
Front Brakes	Dual 210mm discs
Rear Brakes	Dual 210mm discs
Front Tires	27 x 9-14
Rear Tires	27 x 11-14

DIMENSIONS	
Length	120.4 inches
Width	63.0 inches
Height	76.1 inches
Wheelbase	80.2 inches
Bed Size (L x W x H)	36.0 x 55.2 x 10.8 inches
Bed Capacity	1000 pounds (49-state models); 600 pounds (CA model)
Towing Capacity	2500 pounds
Ground Clearance	12.8 inches
Turning Radius	13.8 feet
Curb Weight	1654 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	7.9 gallons

OTHER	
Safety	Recommended for drivers 16 years of age and older.
Available Colors	Matte Green Metallic
Model ID	SXS10M3DT
Seating Capacity	3

FACTORY WARRANTY INFORMATION	
Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2026 American Honda Motor Co., Inc. – Powersports Division